



※ DR, BR, DB, BB, DR2-S, KR2-S SERIES COUPLING




DR SERIES




BR SERIES




DB SERIES




BB SERIES



DR2-S SERIES



KR2-S SERIES



◆ Mechanical Characteristics

Series	d1	d2	D	L	L1	g	M
DR	15	15	25	25	-	2	-
	12	12	22	25	-	2	-
	10	10	20	25	-	2	-
	8	8	20	25	-	2	-
	8	8	18	25	-	2	-
	6	6	18	25	-	2.3	-
	6	6	18	25	-	2.3	-
	5	5	18	25	-	2.3	-
4	4	15	20	-	2.3	-	
DB	8	8	18	25	3.5	-	M3
	10	10	22.5	32	4.5	-	M3
	15	15	38	50	5	-	M4
BB	10	10	22.5	32	3.5	-	M2.5
	15	15	38	50	4.8	-	M4

Series	d1	d2	D	L	L1	g	M	M1
BR	15	15	31	25	-	2	-	-
	12	12	28	25	-	2	-	-
	10	10	26	25	-	2	-	-
	8	8	26	25	-	2.3	-	-
	8	8	24	25	-	2.3	-	-
	6	6	24	25	-	2.3	-	-
	6	6	24	25	-	2.3	-	-
	5	5	24	25	-	2.3	-	-
	4	4	20	25	-	2.3	-	-
	DR2-S	6	6	19	23	3.5	-	M3
8		8	19	23	3.5	-	M3	-
KR2-S	10	10	24	24	3.5	-	M5	M3

◆ Technical Characteristics

Series	Specified torque	Max. torque	Eccentric error	Eccentric angle	Max. speed	Revolve
DR Series	1N.m	2N.m	± 0.2mm	≦ 2.0°	19000min ⁻¹	Synchronous revolve
BR Series	3.5N.m	7N.m	± 0.2mm	≦ 2.0°	6500min ⁻¹	Synchronous revolve
DB Series(D=18)	2N.m	4N.m	± 1mm	≦ 2.0°	20000min ⁻¹	Synchronous revolve
DB Series(D=22.5)	2N.m	4N.m	± 1mm	≦ 2.0°	1800min ⁻¹	Synchronous revolve
DB Series(D=38)	9N.m	18N.m	± 1mm	≦ 2.5°	1000min ⁻¹	Synchronous revolve
BB Series(D=22.5)	2N.m	4N.m	± 1mm	≦ 2.0°	18000min ⁻¹	Synchronous revolve
BB Series(D=38)	9N.m	18N.m	± 1mm	≦ 2.5°	1000min ⁻¹	Synchronous revolve
DR2-S Series(D=19)	0.5N.m	1N.m	± 0.2mm	≦ 2.5°	7000min ⁻¹	Synchronous revolve
DR2-S Series(D=20)	0.5N.m	1N.m	± 0.2mm	≦ 2.5°	8000min ⁻¹	Synchronous revolve
KR2-S Series(D=24)	0.5N.m	1N.m	± 0.2mm	≦ 2.5°	5000min ⁻¹	Synchronous revolve

◆ Ordering code DT-8 × 10-D25L34



Series	Part	Material	Surface treatment	Accessory
DR	-	Hard aluminium alloy	Oxidize treatment on request	Hexagon socket set screws with cup point Hexagon socket head cap screws
BR	-	Hard aluminium alloy	Oxidize treatment on request	Hexagon socket set screws with cup point Hexagon socket head cap screws
DB	Main part	Hard aluminium alloy	Oxidize treatment on request	Hexagon socket set screws with cup point Hexagon socket head cap screws
BB	Connector	Stainless steel bellows	Oxidize treatment on request	Hexagon socket set screws with cup point Hexagon socket head cap screws
DR2-S	-	Engineering plastics	-	Hexagon socket set screws with cup point Hexagon socket head cap screws
KR2-S	-	Engineering plastics	-	Hexagon socket set screws with cup point Hexagon socket head cap screws